



India's Most Preferred Ambulance

Fully Factory Built Ambulance Range I Complies with National Ambulance Code












SALIENT FEATURES


B - Type












Seating: 9+P+D

Seating: 9+P+D







Side wall reinforced to mount Defibrillator, Ventilator, Suction Pump etc.

PECIFICATIONS

	TECHNICAL S
ENGINE	
Model	: FM 2.6 CR ED, BS VI
Туре	: 4 Cyl. Common Rail, DI TCIC
Displacement	: 2596 cc
Max. Output	: 85kW (115hp) @ 2950 rpm
Max. Torque	: 350 Nm @ 1400 - 2200 rpm
TRANSMISSION	
Туре	: G32-5, Synchromesh
No. of Gears	: 5 Forward & 1 Reverse
AXLES	
Front	: Dead Rigid, I-Beam & Reverse Elliot Type
Rear	: Live Rigid
SUSPENSION	

SUSPENSION	
Front	: Semi Elliptical Leaf Springs with Hydraulic Shock Absorber and Anti Roll Bar.

Rear

7 ind 11011 Ball
: Semi Elliptical Leaf Springs with
Hydraulic Shock Absorbers
Anti Roll Bar - optional

STEERING	
Туре	: Power Steering
Brakes	: Hydraulic, dual circuit,
	vacuum assisted ABS with EBD

BRAKES

Front	: DISC
Rear	: Drum
Parking Brake	: Mechanical on rear wheels

WHEELS & TYRES:

(4+1)

: 215/75 R 15 Tyre Size

DIMENSIONS (mm.)

Wheel Base	: 3350
Overall Length	: 5615
Overall Width	: 1900

Overall Height : 2550

Ground Clearance: 200

WEIGHTS (kg.) TYPE (B, C & D)

Max GVW : 3965 Turning Radius : 6.5 M Fuel Tank Capacity: 70 Litres

SEATING CAPACITY

Type B	:9+P+D
Type C	:9+P+D
Type D	:9+P+D

FORCE MOTORS LIMITED

CIN L34102PN1958PLC011172 Mumbai - Pune Road, Akurdi, Pune 411 035. INDIA www.forcemotors.com | Toll Free: 1800 2335 000

NOTE: On account of continuous Research and Development, specifications are subject to change. The data included herein is to be regarded as approximate. Accessories shown may not necessarily be part of standard equipment.





Authorised Dealer: